



011 964 1001
0794499789
www.becksmasonry.co.za
Info@Becksmasonry.co.za

Data Sheet BMP Full Block 20.01.1 / 2 / 3

Data Sheet: Full Block 390x190x140 COTTAGE		
BMP Code	20.01.1	
Description	Full Block	
Pre-Sealer	Chryso Paraflow 20	

Data Sheet: Full Block 390x190x140 EXECUTIVE		
BMP Code	20.01.2	
Description	Full Block	
Pre-Sealer	Chryso Paraflow 20	

Data: Sheet Full Block 390x190x140 FAIR FACE		
BMP Code	20.01.3	
Description	Full Block	
Pre-Sealer	Chryso Paraflow 20	

Properties and Specifications	
Nominal Dimensions (Width x Height x Length mm)	200 x 200 x 400
Actual Dimensions (Width x Height x Length mm)	190 x 190 x 390
Core Volume (% overall thickness)	47 %
Minimum Face Shell Thickness (mm)	32 mm
Average Block Weight (kg)	18
Average Number per Tonne	1620
Number per Pallet	90
Number per m2	12.5
Wall Mass inc. Mortar Hollow (kg/m2)	225
Wall Mass inc. Mortar Core Filled (kg/m2)	416
Durability	General Purpose
Characteristic SANS 10400 Compressive Strength (MPa)	As Per Clients Specifications (7 to 16 MPA)
Fire Rating (Hollow)	60 to 240 / 60 / 60*
Fire Rating (Reinforced and core filled)	60 to 240 / 240 / 240*

This data represents average results from commercial production lots and is for general description purposes only. Figures are accurate at date of publication and subject to change without notice. Contact BMP Masonry for confirmation of product specification.

Fire Resistance Levels as per Australian AS3700:2011.MPA Tested in accordance with: SANS 1215-2008
SANS 10400