



0794499789
Info@Becksmasonry.co.za



BMP Masonry
WhatsApp group



Data Sheet BMP 15.33.3 Breeze

Data Sheet Breeze		
DSM Code	15.33.3	
Description	Breeze Block	
Pre-Sealer	Chryso Paraflow 20	

Properties and Specifications	
Nominal Dimensions (Width x Height x Length mm)	165 x 165 x 165
Actual Dimensions (Width x Height x Length mm)	155 x 155 x 155
Core Volume (% overall thickness)	NA
Minimum Face Shell Thickness (mm)	32 mm
Average Block Weight (kg)	+ - 3.9
Average Number per Tonne	257
Number per Pallet	306
Number per M2	44
Wall Mass inc. Mortar Hollow (kg/m2)	NA
Wall Mass inc. Mortar Core Filled (kg/m2)	NA
Durability	General Purpose
Characteristic SANS 10400 Compressive Strength (MPa)	8.5 MPA Standard
Fire Rating (Hollow)NA	N/A
Fire Rating (Solid Units)N/A	N/A
This data represents average results from commercial production lots and is for general description purposes only. Figures are accurate at date of publication and subject to change without notice. Contact BMP Masonry for confirmation of product specification.	

Fire Resistance Levels as per Australian AS3700:2011.
MPA Tested in accordance with: SANS 1215-2008
SANS 10400